

Gas MD & Gas HD

Standard Gas Item, Packaging, and Load Configurations

GAS MD AND HD COILS STANDARD SIZES, LENGTHS, AND QUANTITIES									
Type	Diameter (inch)	Coil Length (ft)		Pallet Size (in)	Coils/Pallet	Feet/Pallet	Pallets/Truck	Feet/Truck	
		MD	HD						
CTS	0.5	250		48	12	3000	26	78,000	
		500	500	48	12	6000	26	156,000	
	0.75	500		48	8	4000	26	104,000	
	1	250		48	10	2500	26	65,000	
		500	500	48	8	4000	26	104,000	
	1.25	250	250	48	10	2500	26	65,000	
		500	500	60	7	3500	10	35,000	
	IPS	0.5	500	500	48	12	6000	26	156,000
		0.75	150		48	12	1800	26	46,800
			250		48	10	2500	26	65,000
500			500	48	8	4000	26	104,000	
1		150		48	12	1800	26	46,800	
		250		48	10	2500	26	65,000	
		500	500	48	8	4000	26	104,000	
1.25		150		60	10	1500	10	15,000	
		250		60	10	2500	10	25,000	
		500	500	80	7	3500	7	24,500	
1.5		150		60	10	1500	10	15,000	
			500	80	8	4000	7	28,000	
2		150		60	10	1500	10	15,000	
		250	250	80	8	2000	7	14,000	
		500	500	80	7	3500	7	24,500	
3		100		80	8	800	7	5,600	
		150		80	7	1050	7	7,350	
		500		80	3	1500	7	10,500	
4		500	500	80	2	1000	7	7,000	
		1000	1000	Reel	1	1000	12	12,000	
	1400	1400	Reel	1	1400	12	16,800		

Gas MD & Gas HD

Standard Gas Item, Packaging, and Load Configurations

GAS MD AND HD STRAIGHT PIPE STANDARD SIZES, LENGTHS, AND QUANTITIES						
Length (ft)	Diameter (inch)	Joints/Bundle	Bundles/Truck	Joints/Truck	Feet/Bundle	Feet/Truck
20	2	88	26	2288	1760	45,760
	3	63	20	1260	1260	25,200
40	2	88	14	1232	3520	49,280
	3	50	14	700	2000	28,000
	4	29	10	290	1160	11,600
	6	20	10	200	800	8,000
	8	14	8	112	560	4,480
	10	5/4	7/7	63	160/200	2,250
	12	4	12	48	160	1,920
50	4	29	10	290	1450	14,500
	6	20	10	200	100	10,000
	8	14	8	112	700	5,600
	10	5/4	7/7	63	200/250	3,150
	12	4	12	48	200	2,400
	16	3	10	30	150	1,500

Data Sheet

Dimensions & Weights for IPS 0.5"/13mm - 3"/76mm

DIMENSIONS AND WEIGHTS FOR IPS ENDOPOLY 1/2" TO 3" : ALL SIZES & DR'S ASTM D3035, AWWA C901, BNQ 3624-027										
			Wall Thickness (t)				ID ave		PE4710 Weight	
		DR	Min (in)	Max (in)	Min (mm)	Max (mm)	(in)	(mm)	Average (lb/ft)	Minimum (lb/ft)
NPS	3	7	0.500	0.560	12.70	14.22	2.781	70.64	1.48	1.96
		9	0.389	0.436	9.88	11.07	2.941	74.70	1.18	1.58
OD ave (inch)	3.500	11	0.318	0.356	8.08	9.04	3.042	77.27	0.98	1.32
OD min (in)	3.492	13.5	0.259	0.290	6.58	7.37	3.127	79.43	0.81	1.10
OD max (in)	3.508	15.5	0.226	0.253	5.74	6.43	3.175	80.65	0.71	0.97
		17	0.206	0.231	5.23	5.87	3.204	81.38	0.65	0.89
OD ave (mm)	88.9	21	0.167	0.187	4.24	4.75	3.260	82.80	0.53	0.73
OD min (mm)	88.7	26	0.135	0.155	3.43	3.94	3.306	83.97	0.43	0.59
OD max (mm)	89.1	32.5	0.108	0.128	2.74	3.25	3.345	84.96	0.35	0.48